

MV 75 SWING INOX

STAINLESS STEEL INDUSTRIAL VACUUM - SHIFTING CHAMBER - SEALING BARS 620 MM



DESCRIPTION

For all the needs of professional industrial packaging, minipack®-torre is proud to present the **Swing line**, a series of **industrial vacuum packaging machines** that can achieve high speed of operation, thanks to the sliding closure of the chamber. All the machines guarantee the maximum durability and reliability, thanks to the structure in stainless steel AISI 304, a high quality alloy that is often used in the industrial sector.

All the **industrial vacuum packaging machines** in the series are designed and manufactured according to CE regulations, thereby ensuring maximum safety and quality. Ample control possibilities: the digital display allows you to store and manage up to 10 different programs, while an analog volumetric sensor keeps always monitored the vacuum in the chamber and the ATM packing process.



TECHNICAL FEATURES

Electrical power supply	V	400
Phase	ph	3
MAX power installed	kW	7
Dimensions of the sealing bars	mm	620
Vacuum pump	mc/h	160
Machine dimensions with the lid open	mm	1490x1210 h.1340
Machine dimensions with the lid closed	mm	1490x1210 h.1110
Machine weight (Net/Gross)	kg	537/644

minipack®-torre shall not be held liable for typos or printing errors in this catalogue. It also reserves the right to make changes to the specified features without prior notice. All trademarks are property of their respective owners and are hereby acknowledged.

TECHNICAL FEATURES

- o Stainless steel (AISI 304)
- Vacuum cycle with stop
- o Sealing bar with double strip
- o Soft-Air device to ensure controlled air return, provided as standard
- o Vacuum detection with timer
- Filling tables
- o 10 customisable programs
- CE certification.