

MVS52 DV X

DOUBLE TANK TROLLEY VACUUM - SEALING BARS 530 MM



DESCRIPTION

Designed in cooperation with some important chefs, the **MVS X chamber vacuum sealers** line has a series of avant-garde capabilities and highly technological content, with the utmost ease of use. Thanks to the collaboration with industry professionals, this line of **vacuum packaging machines** is equipped with specific functionalities for the needs of professional packaging.

The series models are equipped with a tactile control keypad that avoids any risk of liquid infiltration in the board, thanks to its hermetic application on the front of the bodywork. In addition, with a few touches on the control panel you can access up to 10 customized programs.

A special message on the display notifies you whenever you need to change the oil. In addition, an internal electronic sensor can read the vacuum realized in the chamber. It is also possible to calibrate these **vacuum packaging machines** according to the level of atmospheric pressure at different altitudes.

minipack®-torre S.p.A.

Sede legale - Via Provinciale, 54 - 24044 DALMINE (BG) Italy P.IVA - C.F.: 01633550163 - Capitale sociale 619.200,00 i.v. - Reg. Imprese di Bergamo 01633550163 - REA n. 224151




TECHNICAL FEATURES

Electric power supply	208V 60Hz 3Ph
MAX power installed	3,6 kW (208V 60Hz)
Maximum current	13 A (208V 60Hz)
Dimensions of sealing bars	530 mm (no. 2 side bars per tank - Tot.4)
Packaging cycle (Vacuum 99.9%)	Vacuum= 22 s Air re-immission= 5 s
Vacuum pump	40 mc/h
Work surface height	893 mm
Machine dimensions (lid open)	1278x784x1344 mm
Machine dimensions (lid closed)	1278x784x985 mm
Machine weight (Net/Gross)	268/300 kg
Available chamber dimensions (Tank+lid)	399x519x200 mm (2 tanks)

minipack®-torre shall not be held liable for typos or printing errors in this catalogue. It also reserves the right to make changes to the specified features without prior notice. All trademarks are property of their respective owners and are hereby acknowledged.

TECHNICAL DRAWING



minipack®-torre S.p.A.

Sede legale - Via Provinciale, 54 - 24044 DALMINE (BG) Italy P.IVA - C.F.: 01633550163 - Capitale sociale 619.200,00 i.v. - Reg. Imprese di Bergamo 01633550163 - REA n. 224151



R= Riduttore della pressione del gas / Gas pressure reducer

MVS52DV X

minipack®-torre S.p.A. Sede legale - Via Provinciale, 54 - 24044 DALMINE (BG) Italy P.IVA - C.F.: 01633550163 - Capitale sociale 619.200,00 i.v. - Reg. Imprese di Bergamo 01633550163 - REA n. 224151